



GALVANNEAL    MAXIMUM O.A.L. 422.00"    MAXIMUM O.A.H. 136.00"    SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
2. AIR INLET WITH DISCONNECT COUPLINGS LOCATED ON DRIVER'S SEAT RISER
3. VOGEL LUBE SYSTEM LOCATED BEHIND RIGHT SIDE PUMP PANEL
4. ONE 40" LUMBAR H20 LIGHT STRIP ON BACK OF CAB
5. BRUSHED 5/STL PLATE W/LOGO ON THE RIGHT SIDE OF PUMPHOUSE AREA IPO KNOCKOUTS

REV	DATE	BY	CH	QUANTUM
05NOV21	LME	JJR		PIERCE
09SEP21	LME	JJR		MODEL

		JOB NO.	36554
		SCALE	1:24
<b>TITLE</b> 2000-D-500 WATER/30 FOAM, 152" BODY, SIDE CONTROL (2) CROSSLAYS, (1) DEADLAY, DELUGE, HUSKY 12, HLR		DRAWN BY	LME
		CHECKED BY	NPA
<b>FOR</b> TOWN OF GILBERT GILBERT, ARIZONA		DWG NO.	36554AD-SH1
		SHEET NO.	1 OF 2