



HOSEBED CAPACITIES

①	- 200' OF 1.75\" HOSE
②	- 900' OF 4.00\" HOSE
③	- 600' OF 2.50\" HOSE
④	- 200' OF 2.50\" HOSE

ALUMINUM BODY MAXIMUM O.A.H. 122.00" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. KUSMAUL BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
2. ONE L.E.D. LIGHT STRIP LOCATED ON EACH SIDE IN THE HOSEBED
3. ELECTRIC DOOR LOCK ON DOOR FOR COMPARTMENT B1
4. ADJUSTABLE FULL WIDTH/DEPTH SHELVES THREE IN RS1 AND RS3, TWO IN LS1 AND LS3
5. TWO PAINTED ADJUSTABLE SLIDE-OUT TRAYS IN LS3
6. ONE TILT/SLIDE-OUT TRAY IN LS2
7. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN B1 AND RS3
8. SLIDE-OUT TOOLBOARD WITH PAC TRAC MOUNTING TRACKS IN LS1
9. FIVE DRAWER CTECH ASSEMBLY IN LS1
10. TRANSVERSE PARTITION BETWEEN LS1/B1 AND RS1/B1

11. ONE VERTICAL PARTITION IN COMPARTMENT LS1
12. TRACKS FOR EQUIPMENT MOUNTING LOCATED IN COMPARTMENT RS2
13. AIR INLET/OUTLET W/ DISCONNECT COUPLING ON D.S. PUMP PANEL

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
REV	DATE	BY	CH

		JOB NO. 36656-01-02	
		SCALE 1:24	DATE
TITLE	1500-D-500P, 500 GAL WATER, 30 GAL FOAM TANK, 177\"/>		
FOR	RIALTO FIRE DEPARTMENT RIALTO, CALIFORNIA	CHECKED BY	WKL
DWG NO.	36656AD	SHEET SIZE	D
		SHEET NO.	1 OF 1