



ALUMINUM BODY MAX O.A.H. 12'-3.00" EXCEEDED SIDE ROLL AND FRONTAL IMPACT PROTECTION

- NOTE**
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.
- VANNER BRAVO QBC10 INVERTER IN COMPARTMENT PER SHOP ORDER
 - SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
 - AIR INLET RECESSED WITH DISCONNECT COUPLING ABOVE DRIVERS SIDE FRONT WHEEL
 - BATTERY CHARGER LOCATED IN COMPARTMENT PER SHOP ORDER
 - BATTERY CHARGE INDICATOR LOCATE ON DRIVES SIDE OF CAB
 - ONE 120V 6-PLACE RECEPTACLE IN CAB PER SHOP ORDER
 - RING LIGHTING ON AERIAL LADDER
 - 3.00" RAISED AERIAL PEDESTAL
 - 3-in-1 LYFCOMBO BRACKETS AT AERIAL BASKET
 - 120V POWER TO AERIAL BASKET
 - DC POWER TO AERIAL BASKET
 - WIRELESS CAMERA SYSTEM ON AERIAL BASKET
 - FIRE RESEARCH 3-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP, PUMP PANEL AND TURNTABLE
 - LIMITED RETRACTED 6.00" AERIAL LADDER

CHASSIS DATA		TITLE	100 AERIAL PLATFORM & BODY ASSEMBLY	JOB NO.	36772
MAKE		FOR	500 GALLON WATER TANK	SCALE	1:24
MODEL		FOR	ORANGEBURG FIRE DISTRICT	DRAWN BY	LWE
VELOCITY		DWG NO.	ORANGEBURG, NY	CHECKED BY	NDA
REV	DATE	BY	CH	SHEET SIZE	SHEET NO.
21DEC21	LWE	CSH		D	1 OF 2
22OCT21	LWE	NDA			



36772AD-SH1