



- HOSEBED CAPACITIES**
- ① 200' OF 1.75" D.J. POLY HOSE
 - ② 200' OF 1.75" D.J. POLY HOSE
 - ③ 1200' OF 5.00" D.J. POLY HOSE
 - ④ 600' OF 2.50" D.J. POLY HOSE
 - ⑤ 200' OF 2.50" D.J. POLY HOSE

ALUMINUM BODY SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONE SPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
2. BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
3. BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER
4. DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED PER ORDER
5. SEVEN FULL WIDTH/DEPTH ADJUSTABLE SHELF IN COMPARTMENT PER ORDER
6. TWO FULL WIDTH/DEPTH FLOOR MOUNTED SLIDE-OUT TRAY WITH SIDE SLIDES IN LOCATED PER ORDER
7. PARTITION BETWEEN COMPARTMENTS L51/B1 AND R51/B1
8. TWO PAC TRAC ON BACK WALL OF COMPARTMENT PER ORDER
9. 120V 6-PLACE RECEPTACLE STRIP LOCATED PER ORDER

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
		CHASSIS DATA	TITLE
		MAKE	1500-D-1000P, 161" PUMPER BODY, DELUGE, GENERATOR
		PIERCE	RIGHT SIDE LADDER BRACKETS, (2) X-LAYS, (1) DEADLAY
		MODEL	FOR
		ENFORCER	ROANOKE FIRE EMS
REV	DATE	BY	CH
01DEC21	CDU	CZA	

		JOB NO.	36773
		SCALE	1:24
DRAWN BY KES		DATE	
		CHECKED BY WKL	10NOV21
DWG NO.		SHEET SIZE	D
		SHEET NO.	1 OF 1

36773AD