



MIN A.O.D. 8°  
 MIN A.O.A. 8°  
 ALUMINUM BODY SIDE ROLL AND FRONTAL IMPACT PROTECTION MAX O.A.H. 11'-7.0" MAX O.A.L. 36'-5.25"

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE 2.50 OUTLET WITH 2.50 PIPING AND SWIVEL LOCATED TOP LEFT BUMPER DECK
- SHORELINE RECEPTACLE WITH KUSSMALL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH AIR EJECT AND COVER ON THE DRIVER SIDE FRONT CAB CORNER
- BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
- BATTERY CHARGE INDICATOR LOCATED ON DRIVERS SIDE CAB
- DRIP PAN GUARDS OVER DOOR PER SHOP ORDER
- PULL STRAPS ON COMPARTMENT DOORS PER SHOP ORDER
- CETECH (3) DRAWER ASSEMBLY IN COMPARTMENT PER SHOP ORDER
- WARM WATER RINSE TANK IN CARGO AREA WITH OUTLET ON LEFT SIDE PUMP PANEL
- THREE ADDITIONAL CROSSLAY TRAYS
- ONSPOT AUTOMATIC TIRE CHAINS
- EXTERNAL FOAM SYSTEM
- TWO 120V RECEPTACLES IN CAB PER SHOP ORDER
- TWO 120V RECEPTACLES IN COMPARTMENTS PER SHOP ORDER
- RUNG LIGHTING ON AERIAL LADDER
- NO LIMITED RETRACTION REQUIRED
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNABLE

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
REV	DATE	BY	CH

		JOB NO.	36802
TITLE		SCALE	DATE
FOR		DRAWN BY	280CT21
MODEL		CHECKED BY	03NOV21
ENFORCER		SHEET SIZE	SHEET NO.
		D	1 OF 1

75' HSL AERIAL PUMPER LADDER AND BODY ASSEMBLY  
 500 GALLON TANK-480 GAL. WATER W/20 GAL. FOAM CELL  
 FERN CREEK FIRE PROTECTION DISTRICT  
 LOUISVILLE, KY  
 DWG NO. 36802AD