



- HOSEBED CAPACITIES**
- ① - 1000' OF 4.00" D.J. POLY HOSE
 - ② - 800' OF 2.50" D.J. POLY HOSE
 - ③ - 400' OF 1.75" D.J. POLY HOSE

GALVANNEAL

MAXIMUM O.A.H 118.00"

MAXIMUM O.A.L. 376.00"

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. AIR INLET/OUTLET WITH DISCONNECT COUPLING LOCATED ON LS PUMP PANEL
- 2. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 3. DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- 4. FOAMPRO 2002 FOM SYSTEM

CUSTOMER APPROVAL
 APPROVED BY: _____
 DATE: _____



JOB NO.	36843
SCALE	1:24
DATE	
DRAWN BY	KLE
CHECKED BY	WKL
SHEET SIZE	
SHEET NO.	1 OF 1

CHASSIS DATA	TITLE	1750-D-530P, 500G WATER, 30G FOAM, 152" PUMPER BODY
MAKE	FOR	(3) DEADLAYS, DELUGE, LADDERS BTWN TANK & SIDE SHTS
PIERCE		CITY OF PASADENA
MODEL		PASADENA, CALIFORNIA
DWG NO.		36843AD-SH1