



HOSEBED CAPACITIES

- 950' OF 2.50" D.J. POLY HOSE
- 800' OF 5.00" D.J. POLY HOSE

ALUMINUM BODY

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- AIR INLET/OUTLET WITH DISCONNECT FITTING RECESSED ON DRIVER'S SIDE PUMP PANEL
- BATTERY CHARGER LOCATED IN DRIVER SIDE HATCH COMPARTMENT
- STAINLESS STEEL SCUFFPLATE ON BODY REAR CORNERS
- THREE FULL WIDTH/DEPTH ADJUSTABLE SHELVES LOCATED PER SHOP ORDER
- ONE ADJUSTABLE SLIDE-OUT TRAY LOCATED PER SHOP ORDER
- ONE 18" W RIGHT/ 2" H SIDES ADJUSTABLE TRAY LOCATED PER SHOP ORDER
- FIVE ADJUSTABLE TILTING SLIDE-OUT TRAYS LOCATED PER SHOP ORDER
- ONE FLOOR MOUNTED SLIDE-OUT TRAY LOCATED PER SHOP ORDER
- ONE FULL WIDTH/ DEPTH FLOOR MOUNTED SLIDE OUT TRAY LOCATED PER SHOP ORDER
- TWO SLIDE-OUT TOOLBOARDS WITH PEGBOARD PATTERN AND BRUSHED FINISH LOCATED PER SHOP ORDER
- ONE SWING-OUT ALUMINUM TOOL BOARD W/ AIR PACK STORAGE LOCATED PER SHOP ORDER
- ONE SWING-OUT ALUMINUM TOOL BOARD LOCATED PER SHOP ORDER
- ONE BOLTED HORIZONTAL PARTITION LOCATED PER SHOP ORDER
- PARTITION LOCATED BETWEEN LS1/B1 AND RS1/B1
- THREE VERTICAL PARTITIONS LOCATED PER SHOP ORDER
- TWO DRAWER CTECH DRAWER ASSEMBLY LOCATED PER SHOP ORDER
- PEGBOARD BACK WALL MOUNTED LOCATED PER SHOP ORDER
- 150" OIL DRY HOPPER LOCATED IN LHI/LH2
- TWO AIR BOTTLE HOLDERS W/ CRS STRAPS LOCATED ON THE SWING OUT TOOLBOARD
- HANNAY MODEL SBEF24-23-24 BOOSTER REEL WITH 150' OF 0.75" BOOSTER HOSE IN B1
- TWO 120V DUPLEX RECEPTACLES LOCATED PER SHOP ORDER

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____

REV	DATE	BY	CH	ENFORCER
13JAN22	LST	NPE		

Pierce MANUFACTURING INC.

TITLE: 1500-D-770P, 750 GAL. WATER W/20 GAL. FOAM CELL
189" PUC RESCUE BODY, HYDRAULIC LADDER RACK, HUSKY 3

FOR: ANDERSON FIRE PROTECTION DISTRICT
ANDERSON, CALIFORNIA

DWG NO. 36857AD

JOB NO.	36857
SCALE	1:24
DATE	
DRAWN BY	LST
CHECKED BY	NPE
SHEET SIZE	
SHEET NO.	1 OF 1