



ALUMINUM BODY

MAXIMUM O.A.H. 120.00"

CUSTOMER APPROVAL
 APPROVED BY: _____
 DATE: _____



JOB NO. 36862
 01-02
 SCALE 1:24
 DATE

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- AIR INLET/OUTLET W/ MCMASTER DISCONNECT FITTING ON D.S. PUMP PANEL
- BATTERY CHARGER LOCATED IN CREW CAB SEAT RISER
- BATTERY CHARGER INDICATOR LOCATED NEAR D.S. SEAT RISER WITH BRACKET
- DELTRAN- 4-WAY HYDRANT VALVE MOUNTING PEG LOCATED ON THE D.S. OF THE TAILBOARD
- KEYED LOCK FOR LATCH FOR B1
- FOAM PRO 2001 FOAM SYSTEM
- TRUCK-LITE 35200 RECESSED L.E.D. MARKER LIGHTS IN THE FRONT OF EACH RUNNINGBOARD
- SAMLEX INVERTER IN A BRACKET ON THE DRIVER'S SIDE SEAT RISER

CHASSIS DATA	TITLE	1750-D-500P W/ 30 GAL REMOVABLE FOAM TANK, 132" BODY
MAKE	FOR	(3) DEADLAYS, LADDERS BETWEEN TANK AND S. SHEET
PIERCE		LOS ANGELES CITY FIRE DEPARTMENT
MODEL		LOS ANGELES, CALIFORNIA
REV	DATE	DWG NO. 36862AD-SH1
		SHEET NO. D
		1 OF 2