



ALUMINUM BODY

MAXIMUM O.A.H. 132.00"

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED IN CAB BEHIND DRIVER'S SEAT
- BATTERY CHARGE INDICATOR LOCATED NEAR DRIVER'S SEAT RISER WITH BRACKET
- L.E.D. DUAL LIGHT STRIPS LOCATED IN HOSE BED PER SHOP ORDER
- ONE HANNAY ELECTRIC REWIND CORD REEL MODEL 1618-17-18 WITH 200' OF 10/4 IN HATCH COMPARTMENT RH2
- AUTOMATIC ROD ROTATOR/TIRE CHAINS
- VOSEL 22 POINT LUBE SYSTEM
- WHEEL CHECKS AND MOUNTING BRACKETS PROVIDED BY FIRE DEPARTMENT

REV	DATE	BY	CH	VELOCITY	FR
13MAR23	LME	NPE	CHASSIS DATA		
01SEP22	LME	MGE	MAKE		
29AUG22	LME	MGE	PIERCE		
11JUL22	LME	NPE	MODEL		
06MAY22	LME	NPE			

TITLE	2000-D-770P, 750G WATER W/20G FOAM, 189" BODY, HDRP 3G (3) XLYS, DELUGE, GENERATOR, LADDERS THRU TUNNEL	JOB NO.	36984
FOR	PURCELLVILLE VOLUNTEER FIRE DEPARTMENT PURCELLVILLE, VIRGINIA	SCALE	1:24
DWG NO.	36984AD-SH1	CHECKED BY	NPE
		DRAWN BY	LME
		SHEET SIZE	D
		SHEET NO.	1 OF 2
		DATE	07FEB22
			07FEB22