



**HOSEBED CAPACITIES**  
 ① 200' OF 2.50" D.J. POLY HOSE  
 ② 1000' OF 5.00" D.J. POLY HOSE

ALUMINUM BODY      MAXIMUM O.A.H. 115.00"

SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
2. AIR OUTLET WITH SHUT-OFF VALVE LOCATED ON LEFT SIDE PUMP PANEL
3. BATTERY CHARGER LOCATED BEHIND THE DRIVER'S SEAT
4. DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
5. AIR INLET WITH DISCONNECT COUPLING IN DRIVER'S SIDE STEP WELL
6. HOWLER SIREN SPEAKER SYSTEM MOUNTED BEHIND BUMPER

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
REV	DATE	BY	CH

		TITLE	2000-D-1800P, 184", FULL HEIGHT LS, BROOM RS, FDLER
		FOR	(2) X-LAYS, DELUGE, FOLDING TANK KNOXVILLE FIRE DEPARTMENT KNOXVILLE TENNESSE
DWG NO.	37077AD-SH1	SHEET NO.	1 OF 1

JOB NO.	37077
SCALE	1:24
DATE	
DRAWN BY	BTH
CHECKED BY	SMA
SHEET SIZE	D