



GALVANNEAL MAXIMUM O.A.L. 368.25" MAXIMUM O.A.H. 120.00" SIDE ROLL & FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. CARGO AREA FLOOR SPLIT FOR ACCESS
2. DUAL AMOR L.E.D. HOSED LIGHTS LOCATED BELOW HOSED COVER
3. WHELEN HOWLER AUXILIARY SIREN SPEAKER SYSTEM LOCATED BELOW BUMPER
4. SPECIAL REAR STEP LIGHT LOCATIONS
5. FOUR 20A 120V DUPLEX RECEPTACLES LOCATED IN CAB

CUSTOMER APPROVAL				
APPROVED BY:				
DATE:				
REV	DATE	BY	CH	ARROW XT

Pierce MANUFACTURING INC.

TITLE: 1750-D-520P, 500G WATER, 20G FOAM, 152" FH FRONT & REAR LADDERS BTWN TANK & SS, (2) DEADLAYS, DELUGE

FOR: CITY OF BELLEVUE FIRE DEPARTMENT BELLEVUE, WASHINGTON

DWG NO. 37103AD-SH1

JOB NO.	37103
SCALE	1:24
DATE	
DRAWN BY	JJB
CHECKED BY	MGE
SHEET SIZE	D
SHEET NO.	1 OF 2