

PUMPER
BODY

Long Aluminum 2nd Gen Pumper

CHASSIS
Enforcer Chassis

CHASSIS
AXLE, FRONT, CUSTOM

18,000 Lb Dana Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 5th Gen, 3000 EVS P

BUMPER

19" Extended Stainless Steel

CAB

7010 Enforcer Cab

BODY
WATER TANK

750 Gallon Poly Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, LEFT SIDE

161" Lap Full Height Front & Rear FDLER

COMPT, PUMPER, RIGHT SIDE

161" Lap Full Height Front & Rear FDLER

FIRE SUPPRESSION
PUMPHOUSE

52" Control Zone Top Mount

PUMP

1250 GPM Waterous CS

CROSSLAYS, 1.50"

(2) 1.50" CrossLays Std Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

1.50" SpeedLay Not Required

GENERATOR

Generator Not Required

Foam System

Husky 12 Single Agent Foam System

Foam Cell

25 Gallon Foam Cell, Not Reduced Water

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSMALL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED IN COMPARTMENT PER SHOP ORDER

5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE OF CAB

6. FIVE ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER

7. ONE FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENT PER SHOP ORDER

8. ONE SWING-OUT TOOLBOARD LOCATED PER SHOP ORDER

9. MOUNTING BRACKETS AND WHEEL CHOCKS PROVIDED BY FIRE DEPARTMENT

10. ONE SLIDE-OUT TRAY LOCATED PER SHOP ORDER

