



ALUMINUM BODY

MAXIMUM O.A.H. 144.50"

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____



JOB NO.	37187-01-02
SCALE	DATE
1:24	
DRAWN BY	04MAR22
LWE	
CHECKED BY	04MAR22
SMA	
SHEET SIZE	SHEET NO.
D	1 OF 2

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED IN CREW CAB SEAT RISER
- BATTERY CHARGER INDICATOR LOCATED AT DRIVER'S SIDE STEP AREA
- AIR INLET WITH DISCONNECT COUPLING LOCATED AT DRIVER'S SIDE STEP AREA
- AIR OUTLET WITH SHUT-OFF VALVE LOCATED AT DRIVER'S SIDE STEP AREA
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- JUMPER STUDS AT DRIVER'S SIDE CAB STEP
- ELASTIC PULL STRAP FOR EACH ROLL-UP DOOR
- DRIP PAN GUARD FOR EACH ROLL-UP DOOR
- SIX ADJUSTABLE FULL WIDTH/FULL DEPTH SHELVES IN COMPARTMENTS PER SHOP ORDER
- ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT PER SHOP ORDER
- FOUR FULL WIDTH/DEPTH FLOOR MOUNTED SLIDE-OUT TRAYS WITH SIDE SLIDES IN COMPARTMENTS PER SHOP ORDER
- ONE ALUMINUM SWING-OUT TOOLBOARD WITH PAC TRAC IN COMPARTMENT PER SHOP ORDER
- PAC TRAC ON THE REAR WALL OF COMPARTMENTS PER SHOP ORDER
- TWO 1.00" RETAINING LIPS IN COMPARTMENTS PER SHOP ORDER
- TRIDENT FOLDING STEPS ON AERIAL PENETRATION
- STABILIZERS MODIFIED FOR 18" GROUND PENETRATION
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- 120V POWER TO AERIAL TIP
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNABLE
- CIRCUIT BREAKER PANEL WITH COVER LOCATED IN COMPARTMENT PER SHOP ORDER
- AIR HORN CONTROL AT AERIAL TURNABLE
- 1500 GPM HIGH FLOW WATERWAY
- 14.00 LIMITED RETRACTION ON AERIAL FLY SECTION
- LIFTING EYE ROPE RESCUE ATTACHMENT AT AERIAL TIP
- AERIAL PEDESTAL RAISED 3.00"
- HANNAY ALUMINUM BOOSTER REEL MODEL SBEF20-30-31 WITH 150' OF 1.00 HOSE AND 1.50" PIPING LOCATED ABOVE PUMP WITH THREE ROLLER ASSEMBLIES

CHASSIS DATA	TITLE	107' ASCENDANT AERIAL LADDER AND BODY ASSEMBLY
MAKE	FOR	520 GALLON TANK, 500 GAL. WATER/20 GAL. FOAM
PIERCE	FOR	TULSA FIRE DEPARTMENT
MODEL	FOR	TULSA, OKLAHOMA
VELOCITY	DWG NO.	37187AD-SH1