



HOSEBED CAPACITIES

1	1000' OF 5.00" D.J. POLY HOSE
2	950' OF 2.50" D.J. POLY HOSE
3	300' OF 2.50" D.J. POLY HOSE
4	250' OF 1.88" D.J. POLY HOSE

ALUMINUM BODY

MAXIMUM O.A.L. 348.00"

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER LOCATED BEHIND DRIVER
- DUAL L.E.D. LIGHT STRIPS LOCATED ON THE FRONT OF THE HOSEBED
- DRIP PAN GUARD FOR ROLL-UP DOOR LOCATED IN COMPARTMENTS PER ORDER
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF LOCATED IN COMPARTMENTS PER ORDER
- ONE 120V DUPLEX RECEPTACLE LOCATED IN CAB

		JOB NO.	37359
		SCALE	DATE
TITLE	1500-D-500P, 124" BODY, FULL HEIGHT D.S., LOW P.S. (2) X-LAYS, DELUGE, LADDER RACK, HSH TROUGHS	DRAWN BY	BTH
FOR	CHARLESTON FIRE DEPARTMENT CHARLESTON, SOUTH CAROLINA	CHECKED BY	EGO
DWG NO.	37359AD	SHEET SIZE	SHEET NO.
REV	DATE	BY	CH
ARROW	XT		