

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb Oshkosh Tak-4 Axle

AXLE, REAR

24,000 Lb Meritor Axle

ENGINE

510 HP Paccar MX13

TRANSMISSION

Allison 5th Gen, 4500 EVS P

BUMPER

19" Extended Stainless Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

750 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, DRIVER SIDE

152" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER PASS. SIDE

152" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

48" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

(1) 2.50" Standard Capacity

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Piping For Future Husky 3/12 Foam System

Foam Cell

20 Gallon Foam Cell, Not Reduced Water

Side Roll and Frontal Impact Protection

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CREW CAB

3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL

4. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT

5. BATTER CHARGER INDICATOR LOCATED DRIVER SIDE STEP WELL

6. FIVE ADJUSTABLE SHELVES IN COMPARTMENTS PER SHOP ORDER

7. TWO 120V RECEPTACLES LOCATED PER SHOP ORDER

8. TWO FLOOR MOUNTED TRAYS LOCATED IN COMPARTMENT PER SHOP ORDER

Side View Dimensions:
Overall Length: 119.00 (9'-11") APPROX O.A.H.
Overall Width: 88.00
Wheelbase: 187.50 WB
Ground Clearance: 8.00" NFPA MIN.

Top View Dimensions:
Overall Length: 369.50 (30'-9.50") APPROX OAL
Overall Width: 70.00
Wheelbase: 136.00
Ground Clearance: 19.75 CLEAR, 22.25

Rear View Dimensions:
Overall Width: 86.00
Wheelbase: 42.00
Ground Clearance: 8.00" NFPA MIN.

Component Labels:
- WHELEN FREEDOM IV 81" L.E.D. LIGHTBAR
- RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
- (1) WHELEN M6 L.E.D. WARNING LIGHT
- (1) WHELEN 600 L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE
- (1) H1V1Z FT-B-72 L.E.D. VISOR LIGHT
- MOUNTING PROVISIONS FOR WILL-BURT NIGHT SCAN POWERLITE
- FEDERAL Q2B SIREN
- (2) GROVER AIR HORNS
- WHELEN SA315 SPEAKER WITH STAINLESS STEEL GRILLE
- CENTER HOSE TRAY FOR 125' OF 1.75" HOSE
- RUNNING BOARD HOSE TRAY FOR 30" OF 5.00" HOSE
- (1) FRP L.E.D. LIGHT FOR DESIGNATED WALKING AREA
- (3) H1V1Z FT-GE5M L.E.D. SCENE LIGHTS EACH SIDE
- (2) WHELEN M9 L.E.D. WARNING LIGHTS EACH SIDE
- (2) WHELEN M9 L.E.D. WARNING LIGHTS EACH SIDE
- (2) WHELEN PELCC L.E.D. SCENE LIGHTS
- (1) 2.50" OUTLET
- PIERCE REAR VIEW CAMERA RECESSED
- (1) CUP SWITCH FOR REAR SCENE LIGHTING
- (1) CUP SWITCH FOR HOSE BED LIGHTING
- (2) WHELEN M6 L.E.D. WARNING LIGHTS
- STOP/TAIL LIGHTS
- DIRECTIONAL LIGHTS
- BACK-UP LIGHTS
- (2) HOSE BED DIVIDERS
- DUO- SAFETY LADDER STORAGE
- (1) 24" 2-SECTION 900A
- (1) 14" ROOF 775A
- (1) 10" FOLDING S85A
- (2) ALUMINUM PIKE POLE TUBES
- (1) BACKBOARD (2" X 18" X 72")
- (1) 8" PIKE POLE
- (1) 6" PIKE POLE
- WHELEN TAL65 L.E.D. TRAFFIC DIRECTING LIGHT RECESSED WITH STAINLESS STEEL TRIM

HOSEBED CAPACITY
BED 1
750' OF 3.00" D.J. POLY HOSE
BED 2
1000' OF 5.00" D.J. POLY HOSE
BED 3
250' OF 3.00" D.J. POLY HOSE

CUSTOMER APPROVAL					Pierce MANUFACTURING INC.		JOB NO.	37389
APPROVED BY: _____					TITLE	Pierce Pumper Approval Drawing	SCALE	1:24
DATE: _____							DATE	
				CHASSIS DATA	FOR	Pierce Stock Field Unit	DRAWN BY	MMF
				MAKE			CHECKED BY	THS
				PIERCE	DWG NO.	37389AD	SHEET SIZE	D
				MODEL			SHEET NO.	1 OF 1
REV	DATE	BY	CH	ENFORCER				

View File Created 08-DEC-2021 10:43:11