



- HOSEBED CAPACITIES**
- ① - 400' OF 2.50" D.J. POLY HOSE
 - ② - 1200' OF 5.00" D.J. POLY HOSE
 - ③ - 400' OF 1.75" D.J. POLY HOSE

STAINLESS BODY

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. AUTOMATIC TIRE CHAINS
2. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE PUMP PANEL
3. BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
4. JUMPER STUDS LOCATED ON DRIVER SIDE PUMP PANEL
5. FIVE ADJUSTABLE SHELVES LOCATED PER ORDER
6. ONE FLOOR MOUNTED SLIDE-OUT TRAY LOCATED PER ORDER
7. FIVE 120V RECEPTACLES LOCATED PER ORDER
8. BOLT-IN PARTITIONS BETWEEN COMPARTMENTS L51/B1 & R51/B1

CHASSIS DATA	TITLE	2000-D-1030P, 1000G WATER W/30G FOAM, 152" BODY LADDER BRACKETS RS, (3) HSH, DELUGE, HUSKY 3
MAKE	FOR	FAIRMOUNT FIRE DEPARTMENT SYRACUSE, NEW YORK
PIERCE	DWG NO.	37400AD
MODEL	ENFORCER	
REV	DATE	BY
CH		

PIERCE MANUFACTURING INC.		JOB NO.	37400
		SCALE	1:24
DATE DRAWN BY KLE 27APR22		CHECKED BY	PHA
		02MAY22	
SHEET SIZE D		SHEET NO.	1 OF 1