



ALUMINUM BODY    MAXIMUM O.A.H. 144.00"    MIN A.O.A. 10°    MIN A.O.D. 9.5°

**NOTE**  
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY
- SHORELINE SOAMP RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED IN DRIVER SIDE STEPWELL
- AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- BATTERY CHARGER LOCATED PER ORDER
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER
- SEVEN ADJUSTABLE SHELVES LOCATED PER ORDER
- FOUR FLOOR MOUNTED SLIDE-OUT TRAYS LOCATED PER ORDER
- 3.00" RAISED AERIAL PEDESTAL
- LIFTING EYE ROPE RESCUE ATTACHMENT AT AERIAL TIP
- 1500 GPM HIGH FLOW WATERWAY
- HUSKY 3 FOAM SYSTEM
- 28.00" AERIAL RETRACTION LIMITED

**CUSTOMER APPROVAL**

APPROVED BY: \_\_\_\_\_  
DATE: \_\_\_\_\_

REV	DATE	BY	CH	ENFORCER

**Pierce MANUFACTURING INC.**

JOB NO. 37423  
SCALE 1:24  
DATE \_\_\_\_\_  
DRAWN BY LWE  
CHECKED BY NDA  
SHEET SIZE D  
SHEET NO. 1 OF 1

TITLE: 107' ASCENDANT HSL AERIAL LADDER AND BODY ASSEMBLY  
FOR: 500 GALLON TANK-480 GAL. WATER W/20 GAL. FOAM CELL  
CITY OF DULUTH  
DULUTH, MN

DWG NO. 37423AD