



- HOSEBED CAPACITIES**
- 1100' OF 4.00" D.J. POLY HOSE
 - 800' OF 2.50" D.J. POLY HOSE
 - 150' OF 2.50" D.J. POLY HOSE
 - 150' OF 1.75" D.J. POLY HOSE
 - 150' OF 1.75" D.J. POLY HOSE
 - 400' OF 1.75" D.J. POLY HOSE

STAINLESS STEEL BODY MAXIMUM O.A.L. 352.00" MAXIMUM O.A.H. 113.00"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER MOUNTED BEHIND DRIVER'S SEAT
- BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- TWO FIXED FULL WIDTH/DEPTH SHELVES LOCATED PER ORDER
- ONE FULL WIDTH/DEPTH ADJUSTABLE SHELF LOCATED PER ORDER
- TWO 120V RECEPTACLES LOCATED PER ORDER
- ONSPOT AUTOMATIC TIRE CHAINS

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
CHASSIS DATA	TITLE	1500-D-530P, 500G WATER-30G FOAM, 129" FH LS, LOW RS	
MAKE	FOR	(2) X-LAYS, DELUGE, BOOSTER REEL, LADDER BRACKETS	
PIERCE	FOR	READING DEPARTMENT OF FIRE AND RESCUE SERVICES	
MODEL	DWG NO.	37611AD	
ENFORCER	NO.		



JOB NO.	37611
SCALE	1:24
DATE	
DRAWN BY	BTH
CHECKED BY	CDU
SHEET SIZE	D
SHEET NO.	1 OF 1