



ALUMINUM BODY

MAXIMUM O.A.L. 360.00"

MAXIMUM O.A.H. 122.00"

OVERALL HEIGHT - 122.00"	OVERALL WIDTH - 117.75"	BODY MATERIAL - ALUMINUM
MAX OAL - 372.00"	WHEELBASE - 180.50"	CAB TO AXLE - 110.50"

Pierce MANUFACTURING INC.

JOB NO.	37660
SCALE	1:24
DATE	
DRAWN BY	LME
CHECKED BY	NPE
SHEET SIZE	
SHEET NO.	1 OF 2

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 5/STL SCUFFPLATE ON EACH CAB DOOR JAMB
- BATTERY CHARGER LOCATED BEHIND DRIVERS ON CAB EMS COMPARTMENT
- BATTERY CHARGE INDICATOR LOCATED ON DRIVER'S SEAT RISER
- PULL STRAPS W/FOOTMAN LOOPS FOR SIDE COMPARTMENT DOORS INCLUDING CROSSLAY DOORS
- 12V L.E.D. LIGHT STRIPS LOCATED IN HOSEBED
- 5/STL SCUFFPLATE ON FRONT BULKHEADS
- 5/STL SCUFFPLATE AROUND DEF AND FUEL FILL OPENINGS
- 5/STL SCUFFPLATE ON FRONT CORNERS OF BODY
- 5/STL SCUFFPLATE AROUND AIR BOTTLE COMPARTMENT OPENINGS
- 5/STL SCUFFPLATE ON THE FRONT FACE OF THE CROSSLAY AREA
- 5/STL SCUFFPLATE ON VERTICAL SURFACES OF REAR STEP AREA OF HATCH

- TWO HANNAY BOOSTER REELS MODEL SRF30-23-24 LOCATED IN CARGO AREA EACH WITH 150' OF 1.00" BOOSTER HOSE (NOT INSTALLED)
- WHELEN HOWLER AUXILIARY SIREN (SPEAKER SYSTEM BEHIND RIGHT SIDE OF FRONT BUMPER)
- WHELEN M5 L.E.D. DIRECTIONAL LIGHTS
- 5/STL SCUFFPLATES REAR CAB CORNERS
- 5/STL SCUFFPLATES REAR BODY CORNERS

REV	DATE	BY	CH	ENFORCER

CHASSIS DATA

TITLE 1500-D-780, 750 GAL WATER W/30 GAL FOAM, 177" RESCUE (4) XLAYS, DELUGE, BOOSTER REELS, LADDERS THRU BODY

FOR COUNTY OF MAUI FIRE DEPARTMENT MAUI, HAWAII

DWG NO. 37660AD-SH1