



**HOSEBED CAPACITIES**

- 250' OF 2.50" D.J. POLY HOSE
- 250' OF 2.50" D.J. POLY HOSE
- 300' OF 3.00" D.J. POLY HOSE (DEAD LOAD)
- 1000' OF 5.00" D.J. POLY HOSE
- 500' OF 3.00" D.J. POLY HOSE (DEAD LOAD)

**ALUMINUM BODY**

**NOTE**  
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- AIR INLET/OUTLET WITH DISCONNECT FITTING LOCATED IN PUMP PANEL
- KUSSMAUL BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- TEN FULL WIDTH/DEPTH ADJUSTABLE SHELVES IN COMPARTMENTS PER ORDER
- ONE ADJUSTABLE SLIDE-OUT TRAY IN COMPARTMENT PER ORDER
- ONE ADJUSTABLE TILTING SLIDE-OUT TRAY IN COMPARTMENT PER ORDER
- THREE FLOOR MOUNTED SLIDE-OUT TRAYS IN COMPARTMENTS PER ORDER
- CTECH 3-DRAWER ASSEMBLY IN COMPARTMENT PER ORDER
- TWO SLIDE-OUT ALUMINUM TOOL BOARDS IN COMPARTMENTS PER ORDER
- ONE SWING-OUT ALUMINUM TOOL BOARD IN COMPARTMENT PER ORDER
- PARTITION BETWEEN COMPARTMENTS LS1/B1 AND RS1/B1
- ONE VERTICAL PARTITION IN COMPARTMENT PER ORDER
- ONE VERTICAL PARTITION IN HATCH PER ORDER
- CIRCUIT BREAKER PANEL IN COMPARTMENT PER ORDER
- HANNAY ELECTRIC REWIND CORD REEL WITH QTY OF 200' OF 12/3 CABLE LOCATED IN B1 COMPARTMENT (MODEL 1618-17-18)
- HANNAY BOOSTER REEL FOR 150' OF .75" HOSE LOCATED IN CARGO AREA LEFT SIDE WITH COVER (MODEL: EF24-23-24)
- FOUR 120V DUPLEX RECEPTACLES LOCATED PER ORDER

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
CHASSIS DATA	TITLE	2000-D-800P, 780G WATER-20G FOAM, 161" FHD, FDLER RS (3) SPDLAY, BOOSTER REEL, CABLE REEL, GENERATOR	
MAKE	FOR	ROCKINGHAM COUNTY HARRISONBURG, VIRGINIA	
PIERCE			
MODEL	DWG NO.	37710AD	
REV	DATE	BY	CH
			ENFORCER

		JOB NO.	37710
		SCALE	DATE
		DRAWN BY	BTH
		CHECKED BY	CDU
		SHEET SIZE	SHEET NO.
		D	1 OF 1