



- HOSEBED CAPACITIES**
- ① 250' OF 2.50" D.J. POLY HOSE (PRECONNECTED)
 - ② 800' OF 5.00" D.J. POLY HOSE
 - ③ 500' OF 2.50" D.J. POLY HOSE (PRECONNECTED)

ALUMINUM BODY MAXIMUM O.A.L. 428.25" SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. LIGHT TOWER CONTROLLER LOCATED PER ORDER
- 2. BATTERY CHARGER LOCATED PER ORDER
- 3. BATTERY CHARGER INDICATOR LOCATED PER ORDER
- 4. AMDR AY-LB-12HWO WALKING SURFACE LIGHTS LOCATED PER ORDER

REV	DATE	BY	CH	VELOCITY
27MAR24	BST	CSH		CHASSIS DATA
10JAN24	BST	CSH		MAKE
06OCT23	BTH	PHA		PIERCE
03OCT23	BTH	CSH		MODEL
02OCT23	BTH	CSH		

		JOB NO.	37954
		SCALE	1:24
TITLE 1500-D-750P, 189" HDRP 3G BODY, DELUGE, LIGHT TOWER LADDERS THRU BODY, 48" SIDE CONTROL	FOR BERLIN FIRE DEPARTMENT BERLIN, CONNECTICUT	DRAWN BY	BST
		CHECKED BY	PHA
DWG NO. 37954AD-SH1	DATE 17APR23	SHEET SIZE	D
		SHEET NO.	1 OF 2