



ALUMINUM BODY
 MIN. ANGLE OF APPROACH 15°-LOADED MIN. ANGLE OF DEPARTURE 15°-LOADED SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER
- BATTERY CHARGER LOCATED BEHIND PASSENGER'S SEAT PER ORDER
- DC POWER TO AERIAL TIP
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNTABLE
- LIFTING EYE ROPE RESCUE ATTACHMENT AT AERIAL TIP
- LIFT EYES LOCATED AT THE END OF THE BASE SECTION EACH SIDE
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- ONE ZIAMATIC SAC-44-E FOLDING WHEEL CHOCK SHIPPED LOOSE
- MOUNTING BRACKET FOR AKRON LADDER PIPE LOCATED PER ORDER
- TRIDENT FOLDING STEPS ON AERIAL DEVICE
- AERIAL BOOM SUPPORT RAISED 2.00"

		JOB NO.	38053
		SCALE	1:24
TITLE 107 ASCENDANT AERIAL TILLER AND BODY ASSY NO PUMP/NO TANK.		DATE	
		DRAWN BY	SHU
FOR CITY OF DAVIS DAVIS, CA		CHECKED BY	NDA
		DATE	16MAR23
DWG NO. 38053AD-SH1		SHEET SIZE	SHEET NO.
		D	1 OF 2