



(ALUMINUM BODY) (MAXIMUM O.A.H. 120.00") (MAXIMUM O.A.L. 380.25") (SIDE ROLL AND FRONTAL IMPACT PROTECTION)

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. AIR OUTLET W/ SHUT OFF VALVE LOCATED ON DS PUMP PANEL
- 2. REVERSED HINGED DOOR ON COMPARTMENT L53
- 3. BATTERY CHARGER LOCATED IN CREW CAB SEAT RISER
- 4. AMOR DUAL LED LIGHT STRIPS IN HOSE BED

REV	DATE	BY	CH	ENFORCER
060C123	LME	BSE		CHASSIS DATA
31AUG23	LME	BSE		MAKE
19JUN23	LME	BSE		PIERCE
12JUN23	LME	BSE		MODEL
24APR23	LME	BSE		

		JOB NO.	38058 (01-05)
		SCALE	1:24
TITLE	2000-D-730P, 700 WATER W/30 FOAM, 145" SPCL PUMPER (4)XLAYS, DELUGE, BOOSTER REEL, HYD. LADDER RACK	DRAWN BY	LME
FOR	PUGET SOUND REGIONAL FIRE AUTHORITY KENT, WASHINGTON	CHECKED BY	JBL
DWG NO.	38058AD-SH1	SHEET SIZE	D
		SHEET NO.	1 OF 1