

PUMPER

BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Enforcer Chassis

CHASSIS

AXLE, FRONT, CUSTOM

19,500 Lb TAK-4 Axle

AXLE, REAR

27,000 Lb Dana Axle

ENGINE

450 HP Cummins L9 Engine

TRANSMISSION

Allison 6th Gen, 3000 EVS P

BUMPER

19" Extended Painted Steel

CAB

7010 Enforcer Cab

BODY

WATER TANK

750 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, LEFT SIDE

152" Lap Full Height Front & Rear FDLER

COMPT, PUMPER, RIGHT SIDE

152" Lap Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

52" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" 200' of 2.00"

CROSSLAYS, 2.50"

(1) 2.50" 250' of 2.00"

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Husky 3 Single Agent Foam System

Foam Cell

25 Gallon Foam Cell, Not Reduced Water

Side Roll and Frontal Impact Protection

NOTE

DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OUTLET WITH 2.00 PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY.

2. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB

3. AIR INLET/OUTLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPNELL

4. BATTERY CHARGER LOCATED PER ORDER

5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER

6. SIX ADJUSTABLE SHELVES LOCATED PER ORDER

7. FOUR FLOOR MOUNTED SLIDE-OUT TRAY LOCATED PER ORDER

8. ONE SWING-OUT TOOLBOARD LOCATED PER SHOP ORDER

9. AUTOMATIC TIRE CHAINS

Side View Labels:

- 128.00 (10'-8") APPROX O.A.H.
- (1) TECNIG E960 L.E.D. CORNERING/SCENE LIGHT EACH SIDE
- FIRE RESEARCH MAX VISION L.E.D. WATER LEVEL GAUGE EACH SIDE
- 5/8" LIGHT SHIELD
- FREE FLOATING RUNNING BOARD HOSE TRAY FOR XX" OF X.XX" HOSE
- HANNAY BOOSTER REEL (EF24-28-29) FOR 200' OF 1.00" BOOSTER HOSE
- (1) SIDE VIEW CAMERA EACH SIDE

Top View Labels:

- (1) WHELEN E960 L.E.D. CORNERING/SCENE LIGHT EACH SIDE
- (1) WHELEN M6 L.E.D. WARNING LIGHT
- (1) WHELEN M62T L.E.D. DIRECTIONAL LIGHT IN A COMMON BEZEL EACH SIDE
- (1) WHELEN SA315P SPEAKER WITH 5/8" STL GRILLE
- (2) BORES 848-211 LIGHTED SIGHT RODS
- (3) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE
- (1) WHELEN TAL65 L.E.D. TRAFFIC DIRECTING LIGHT RECESSED
- (2) WHELEN PFBP12C L.E.D. DECK LIGHTS
- (2) WHELEN ROTA-BEAM R316 BEACON LIGHTS
- (2) HOSE BED DIVIDERS
- (2) HIVIZ FT-MB-2.6 L.E.D. SCENE LIGHTS
- (1) 2.50" OUTLET
- (1) CUP SWITCH FOR DS HIVIZ LIGHT
- (1) CUP SWITCH FOR HOSEBED LIGHTS
- (1) CUP SWITCH FOR REAR DECK LIGHTS
- (2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS
- (1) CUP SWITCH FOR PS HIVIZ LIGHT
- 5.00" INLET/OUTLET WITH 5.00" PIPING
- PIERCE REAR VIEW CAMERA RECESSED

Dimensions (Top View):

- 72.00, 10.50, 62.00, 52.00, 84.00, 72.00, 10.50, 62.00, 30.25 CLEAR, 32.75

Side View Dimensions:

- 88.00, 70.00, 191.50 WB, 369.25 (30'-9.25") APPROX OAL

HOSEBED CAPACITY:

- BED 1**
300' OF 1.75" D.J. POLY HOSE (ABOVE)
600' OF 2.50" D.J. POLY HOSE (BELOW)
- BED 2**
1200' OF 5.00" D.J. POLY HOSE
- BED 3**
100' OF 3.00" D.J. POLY HOSE
- BED 4**
600' OF 2.50" D.J. POLY HOSE

REAR View Labels:

- (1) HIVIZ FT-B-72 L.E.D. VISOR LIGHT
- (1) FEDERAL Q2B SIREN
- (2) AIR HORNS
- LEFT HOSE TRAY FOR 100' OF 1.75" HOSE
- CENTER HOSE TRAY FOR 100' OF 1.75" HOSE

Dimensions (Rear View):

- 14.25, 33.50, 6.38, 13.87, 26.00, 46.50, 35.50, 24.00, 36.00, 43.75, 72.00, 98.00, 36.00, 43.75, 72.00, 98.00, 14.00, 68.00, 14.00, 28.00, 40.00, 28.00, 96.00

CUSTOMER APPROVAL				Pierce MANUFACTURING INC.		JOB NO.	38067
APPROVED BY: _____						SCALE	1:24
DATE: _____						DATE	
			CHASSIS DATA	TITLE	Pierce Pumper Approval Drawing		
			MAKE	FOR	Rocky Point Fire District		
			PIERCE				
			MODEL	DWG NO.	38067AD		
REV	DATE	BY	CH	ENFORCER		SHEET SIZE	SHEET NO.
						D	1 OF 1

View File Created 14-JUN-2022 12:44:47