



- HOSEBED CAPACITIES**
- ① 200' OF 1.75" D.J. POLY HOSE
 - ② 200' OF 2.50" D.J. POLY HOSE
 - ③ 800' OF 4.00" D.J. POLY HOSE
 - ④ 500' OF 2.50" D.J. POLY HOSE
 - ⑤ 200' OF 2.50" D.J. POLY HOSE
 - ⑥ 200' OF 1.75" D.J. POLY HOSE

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. RUD AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- 2. AIR INLET W/ DISCONNECT FITTING LOCATED ON DS PUMP PANEL
- 3. AIR OUTLET W/ SHUT OFF VALVE LOCATED ON DS PUMP PANEL
- 4. LUBE SYSTEM PUMP LOCATED PER SHOP ORDER
- 5. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT
- 6. TWO AMOR DUAL L.E.D. STRIP LIGHTS LOCATED BELOW HOSEBED COVER
- 7. TWO AMOR L.E.D. STRIP LIGHTS IN THE INTERIOR CARGO AREA
- 8. ONE 120V RECEPTACLE LOCATED IN CAB PER ORDER

REV	DATE	BY	CH	VELOCITY
30AUG24		KLE	JLL	PIERCE
07MAR24		ARI	JLL	MODEL

		JOB NO.	38092-01-02
		SCALE	1:24
TITLE 2000-D-550P, 520G WATER/30G FOAM, 152" BODY DELUGE, BOOSTER REEL, RS LADDER BRACKETS		DATE	15JUN23
		FOR	OLATHE FIRE DEPARTMENT OLATHE, KANSAS
DWG NO. 38092AD-SH1		CHECKED BY	WKL
		SHEET SIZE	D
		SHEET NO.	1 OF 2