



| | | | | | | | | | | | | |
|--|---|---|---|--|--|--|---|--------------------------|-------|-------|---------|-------|
| CHASSIS Enforcer Chassis ENGINE 500 HP Cummins X12 Engine | CAB 7000 Enforcer Cab BUMPER 15" Extended Painted Aluminum | AXLE, FRONT, CUSTOM 24,000 Lb TAK-4 Axle AXLE, REAR 54,000 Lb Meritor Axle | TRANSMISSION Allison 5th Gen, 4500 EV5 P | PUMPHOUSE 42" Control Zone Side Mount PUMP 2000 GPM Waterous S100 | CROSSLAYS, 1.50" (2) 1.50", 200' of 1.75" Hose CROSSLAYS, 2.50" 2.50" Crosslay Not Required | SPEEDLAYS Speedlays Not Required GENERATOR Generator Not Required | SAFETY Side Roll and Frontal Impact Protection | CUSTOMER APPROVAL | | | JOB NO. | 38115 |
| | | | | | | | | APPROVED BY: | DATE: | SCALE | DATE | |
| NOTE DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN. | 1. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE FRONT CORNER OF THE CAB 2. AIR INLET WITH DISCONNECT COUPLING IN A RECESSED ALUMINUM TREADPLATE BOX IN THE DRIVER SIDE STEPWELL 3. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT 4. BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER 5. SIX ADJUSTABLE FULL WIDTH/FULL DEPTH SHELVES IN COMPARTMENTS PER ORDER 6. FOUR SLIDE-OUT FLOOR MOUNTED TRAYS IN COMPARTMENTS PER ORDER 7. L.E.D. LIGHT STRIPS WITH STAINLESS STEEL PROTECTIVE COVER LOCATED IN HOSE BED 8. NON-RAISED AERIAL PEDESTAL 9. DC POWER TO AERIAL TIP 10. 3-IN-1 LYFE BRACKETS AT AERIAL BASKET | | 11. FOUR FLOOR MOUNTED SLIDE-OUT TRAY IN COMPARTMENTS L52, L54, R52, R54 12. TECNO L.E.D. RUNG STYLE LIGHTING ON AERIAL LADDER SECTIONS PER ORDER 13. ATKINSON 2-WAY INTERCOM SYSTEM BETWEEN PLATFORM & TURNTABLE | | | Pierce MANUFACTURING INC. | | | | | | |
| | TITLE 100' ASCENDANT AERIAL TOWER AND BODY ASSEMBLY MAKE PIERCE FOR PIERCE FIELD UNIT APPLETON, WI MODEL DWG NO. 38115AD | DRAWN BY ANZ CHECKED BY THS SHEET SIZE D SHEET NO. 1 OF 1 | | | | | | | | | | |