



BODY 110' Single Axle Platform Aluminum Body	WATER TANK 500 Gallon Poly Water Tank
COMPT, LEFT SIDE FRONT Full Height RollUp Forward	Foam System Foam System Not Required
COMPT, LEFT SIDE REAR Full Height RollUp Rearward	Foam Cell Foam Cell Not Required
COMPT, RIGHT SIDE FRONT Full Height RollUp Forward	
COMPT, RIGHT SIDE REAR Full Height RollUp Rearward-Large Rear	

CHASSIS Enforcer Chassis 450 HP Cummins L9 Engine	CAB 7010 Notched Enforcer Cab BUMPER 19" Extended Painted Steel	AXLE, FRONT, CUSTOM 22,800 Lb TAK-4 Axle AXLE, REAR 33,500 Lb Meritor Axle	TRANSMISSION Allison 6th Gen, 3000 EV5 P	PUMPHOUSE 52" Control Zone Side Mount PUMP 2000 GPM Waterous CSU	CROSSLAYS, 1.50" (2) 1.50" Standard Capacity CROSSLAYS, 2.50" (1) 2.50" Standard Capacity	SPEEDLAYS Speedlays Not Required GENERATOR Generator Not Required	-	-
--	--	---	--	---	--	--	---	---

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- KUSSMAUL BATTERY CHARGER LOCATED IN CAB PER ORDER
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- SIX PULL STRAPS WITH SPECIAL LENGTH ON DOOR IN COMPARTMENTS PER ORDER
- SEVEN ADJUSTABLE FULL WIDTH/FULL DEPTH SHELVES IN COMPARTMENTS PER ORDER
- L.E.D. LIGHTING ON AERIAL LADDER SECTIONS
- 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP OR PLATFORM AND TURNABLE
- BREATHING AIR TO AERIAL TIP
- 1250 GPM HIGH FLOW WATERWAY
- AIR INLET WITH DISCONNECT COUPLING LOCATED ON DRIVERS SIDE PUMP PANEL PER ORDER
- AERIAL LIMITED RETRACTION NOT REQUIRED

Pierce MANUFACTURING INC.		JOB NO.	38406
TITLE		SCALE	DATE
FOR		CHECKED BY	28JUL22
DWG NO.		SHEET SIZE	SHEET NO.
38406AD		D	1 OF 1

REV	DATE	BY	CH	ENFORCER
06FEB23	SHU	CLM		
20DEC22	SHU	CLM		