


BODY 100' Ascendant Aerial Tower Alum Body COMPT, DRIVER SIDE Full Height RollUp Doors COMPT, PASSENGER SIDE Full Height RollUp Doors	WATER TANK 300 Gallon Poly Water Tank Foam System Foam System Not Required Foam Cell Foam Cell Not Required
---	---



CHASSIS Enforcer Chassis 605 HP Cummins X15 Engine	CAB 7000 Enforcer Cab 15" Extended Painted Aluminum	AXLE, FRONT, CUSTOM 24,000 Lb TAK-4 Axle AXLE, REAR 52,640 Lb TAK-4 T3 Axle	TRANSMISSION Allison 6th Gen, 4500 EV5 P	PUMPHOUSE 42" Control Zone Side Mount PUMP 2000 GPM Waterous S100	CROSSLAYS, 1.50" (2) 1.50", 200' of 1.75" Hose CROSSLAYS, 2.50" 2.50" Crosslay Not Required	SPEEDLAYS Speedlays Not Required GENERATOR Generator Not Required	SAFETY Side Roll and Frontal Impact Protection	CUSTOMER APPROVAL APPROVED BY: _____ DATE: _____		JOB NO. 38717
NOTE DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.									TITLE 100' ASCENDANT AERIAL TOWER AND BODY ASSEMBLY	SCALE 1:24 DATE 27SEP22
1. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE FRONT CORNER OF THE CAB 2. AIR INLET WITH DISCONNECT COUPLING IN A RECESSED ALUMINUM TREADPLATE BOX IN THE DRIVER SIDE STEPWELL 3. BATTERY CHARGER LOCATED BEHIND DRIVER'S SEAT 4. BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER 5. SIX ADJUSTABLE FULL WIDTH/FULL DEPTH SHELVES IN COMPARTMENTS PER SHOP ORDER 6. FOUR SLIDE-OUT FLOOR MOUNTED TRAYS IN COMPARTMENTS PER SHOP ORDER 7. L.E.D. LIGHT STRIPS LOCATED IN THE HOSE BED PER SHOP ORDER 8. NON-RAISED AERIAL PEDESTAL 9. DC POWER TO AERIAL TIP 10. 3-IN-1 LYFECOMBO BRACKETS AT AERIAL BASKET 11. RUNG LIGHTING ON AERIAL LADDER 12. 2-WAY INTERCOM SYSTEM BETWEEN AERIAL TIP AND TURNABLE									FOR PIERCE FIELD UNIT APPLETON, WI	CHECKED BY THS DATE 27SEP22
REV DATE BY CH									DWG NO. 38717AD	SHEET SIZE D SHEET NO. 1 OF 1