



BODY Pumper, HDRP, Aluminum	WATER TANK 1000 Gallon Poly Water Tank
COMPT, LEFT SIDE 177" Rollup Full Height & Depth Front & Rear	Foam System Husky 3 Single Agent Foam System
COMPT, RIGHT SIDE 177" Rollup Full Height & Depth Front & Rear	Foam Cell 30 Gallon Foam Cell, Not Reduced Water
COMPT, REAR 29.50" FF Rollup Rear Compt w/Tailboard	

HOSEBED CAPACITY	
BED 1	450' OF 5.00" D.J. POLY HOSE
BED 2	500' OF 3.00" D.J. POLY HOSE
BED 3	400' OF 1.75" D.J. POLY HOSE

CHASSIS Enforcer Chassis 450 HP Cummins L9 Engine	CAB 7010 Enforcer Cab 19" Extended Stainless Steel	AXLE, FRONT, CUSTOM 20,000 Lb Dana Axle	TRANSMISSION Allison 6th Gen, 3000 EV5 P	PUMPHOUSE 45" Control Zone Side Mount 1250 GPM Waterous CXC20	CROSSLAYS, 1.50" 1.50" Crosslays Not Required	SPEEDLAYS (2) 1.50" Speedlays Std. Cap. Generator Not Required	SAFETY Frontal Impact Protection
ENGINE	BUMPER	AXLE, REAR 27,000 Lb Dana Axle		PUMP	CROSSLAYS, 2.50" 2.50" Crosslay Not Required		

Pierce MANUFACTURING INC.		JOB NO.	38963
TITLE		SCALE	DATE
Pierce Pumper Approval Drawing		1:24	24APR23
FOR		CHECKED BY	24APR23
St Charles Fire Department		COL	
DWG NO.		SHEET SIZE	SHEET NO.
38963AD-SH1		D	1 OF 1

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONE 1.50" OUTLET WITH 2.00" PIPING AND SWIVEL LOCATED IN CENTER BUMPER TRAY
- SHOULDER RECEPTACLE WITH KUSSMALL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- AIR INLET WITH KUSSMALL AIR EJECT ON DRIVER SIDE ABOVE FRONT TIRE
- BATTERY CHARGER LOCATED PER ORDER
- BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER
- SIX ADJUSTABLE SHELVES LOCATED PER ORDER
- FOUR FLOOR MOUNTED TRAYS LOCATED PER SHOP ORDER
- ONE CTECH THREE DRAWER ASSEMBLY LOCATED PER SHOP ORDER
- ONE SWING-OUT TOOLBOARD LOCATED PER SHOP ORDER
- AUTOMATIC TIRE CHAINS

REV	DATE	BY	CH	ENFORCER
160C123	MMF	COS		CHASSIS DATA
12SEP23	MMF	COS		MAKE
11JUL23	MMF	COS		PIERCE
10JUL23	WRE	COS		MODEL
22JUN23	MMF	COS		