

Enforcer Chassis

27,000 lb Meritor Axle

510 HP Paccar MX13 Engine

ALLison 5th Gen, 4000 EVS P

22" Extended Painted Steel

7010 Enforcer Cab

30.75" FF Rollup Rear Comp

152" Rollup Full Height Front & Rear FDLER

152" Rollup Full Height Front & Rear FDLER

1500 GPM Dar-Ley PSM

(2) 1.50" Standard Capacity

(1) 2.50" Standard Capacity

Speedlays Not Required

Generator Not Required

FoamPro 160C

20 Gal Foam Cell Not Reducing

DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

1. ONE 1.50 OULET WITH 2.00 PIPING AND SWIVEL LOCATED ON TOP BUMPER RIGHT SIDE
2. SHORELINE RECEPTACLE WITH KUSMAUL SWIVEL ABOVE E-JECT LOCATED ON DRIVER SIDE OF THE CAB
3. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
4. BATTERY CHARGER LOCATED PER ORDER
5. BATTERY CHARGE INDICATOR LOCATED ON THE DRIVER SIDE SEAT RISER
6. SIX ADJUSTABLE SHELVES LOCATED PER ORDER
7. JUMPER STUDS DRIVER SIDE CAB STEP
8. WHEEL CHOCKS AND MOUNTING PROVIDED BY FIRE DEPARTMENT

SHEET SIZE	SHEET NO.
D	1 OF 1