

PUMPER
BODY

Medium Aluminum 2nd Gen Pumper

CHASSIS

Saber FR Chassis

CHASSIS

AXLE, FRONT, CUSTOM

18,000 Lb TAK-4 Axle

AXLE, REAR

24,000 Lb Meritor Axle

ENGINE

380 HP Cummins L9 Engine

TRANSMISSION

Allison 6th Gen, 3000 EVS P

BUMPER

22" Extended Painted Steel

CAB

7010 Saber FR Cab

BODY

WATER TANK

750 Gallon New York Style Water Tank

COMPT, PUMPER, REAR

30.75" FF RollUp Rear Compt

COMPT, PUMPER, LEFT SIDE

152" RollUp Full Height Front & Rear FDLER

COMPT, PUMPER, RIGHT SIDE

152" RollUp Full Height Front & Rear FDLER

FIRE SUPPRESSION

PUMPHOUSE

45" Control Zone Side Mount

PUMP

1500 GPM Waterous CSU

CROSSLAYS, 1.50"

(2) 1.50" Standard Capacity

CROSSLAYS, 2.50"

2.50" Crosslay Not Required

SPEEDLAYS

Speedlays Not Required

GENERATOR

Generator Not Required

Foam System

Husky 3 Foam System

Foam Cell

20 Gal Foam Cell Not Reduce

Side Roll and Frontal Impact Protection

Labels and Dimensions:

- Side View:**
 - 125.00 (10'-5") APPROX O.A.H.
 - (2) WIONSMC L.E.D. WARNING LIGHTS EACH SIDE
 - (2) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE
 - 3.00" DELUGE OUTLET WITH X618 11FT EXTEND-A-GUN AND VULCAN 8500 ELKHART MONITOR (CTF)
 - HUSKY 3 FOAM SYSTEM
 - (2) CROSSLAY HOSE BEDS FOR 200' OF 2.00" HOSE WITH 2.00" PIPING
 - (1) CROSSLAY HOSE BEDS FOR 200' OF 1.75" HOSE WITH 2.00" PIPING
 - FIRE RESEARCH MAX VISION L.E.D. WATER LEVEL GAUGE EACH SIDE
 - FRONT CROSS VIEW 8.00" CONVEX MIRROR
 - RETRAC HEATED/REMOTE CONTROL MIRRORS WITH CONVEX SECTION
 - (3) WHELEN FREEDOM IV ROTA-BM 23" LED LIGHTBARS
 - (2) WHELEN 6RB L.E.D. WARNING LIGHTS A COMMON BEZEL EACH SIDE
 - 2.50" FRONT OUTLET W/2.50" PLUMBING
 - (2) WHELEN M6 L.E.D. WARNING LIGHTS
 - (4) WHELEN M6 L.E.D. WARNING LIGHTS EACH SIDE RECESSED
 - (2) AIR HORNS
 - (2) WHELEN 5A315P SPEAKERS WITH 5/STL GRILLE
 - CENTER HOSE TRAY FOR 150' OF 1.75" HOSE
 - RAINING BOARD HOSE TROUGHS FOR 25' OF 5.00" SOFT SUCTION HOSE
 - 21.25
 - 18.62 CLEAR
 - 70.00
 - 62.00
 - 90.00
- Top View:**
 - (2) WHELEN L31HRFN L.E.D. WARNING LIGHTS
 - (2) WHELEN M6 WARNING LIGHTS
 - HIVIZ FT-65M SCENE LIGHTS
 - FIRE RESEARCH MAX VISION L.E.D. WATER LEVEL GAUGE
 - (2) 2.50" OUTLETS
 - (1) CUP SWITCH FOR REAR SCENE LIGHTS
 - (1) CUP SWITCH FOR HOSEBED LIGHTS
 - (2) WHELEN M6 L.E.D. WARNING LIGHTS STOP/TAIL LIGHTS DIRECTIONAL LIGHTS BACK-UP LIGHTS MOUNTED IN WHELEN M6 PIERCE BEZELS
 - (2) 0.25" SINGLE SHEET HOSE BED DIVIDERS
 - (1) LONG TOOL STORAGE COMPARTMENT
 - DUO-SAFETY LADDER STORAGE
 - (1) 24" 2-SECTION 900A
 - (1) 14" ROOF 775DR
 - (1) 10" FOLDING 585A
 - (2) ALUMINUM PIKE POLE TUBES
 - 5'-7"
 - 86.50
 - 72.00
 - 14.50
 - 13.87
 - 11.63
 - 33.00
 - 9.50
 - 40.50
 - 31.50
 - 1.75
 - 4.00
 - 36.00
 - 30.75
 - 81
 - 14.00
 - 28.00
 - 68.00
 - 40.00
 - 28.00
 - 96.00
 - 16.00
 - 86.00
 - 58.00
 - 57.50 FC
 - 35.50
 - 31.50
 - 2.25
 - 27.13
 - 4.00
 - 61.00
 - 55.50
 - 30.00
 - 64.75
 - 22.00
 - 47.50
 - 3.00
 - 8.00" NFPA MIN.
 - 3.25
 - 8.00" NFPA MIN.
 - 20.00
 - 79.25
 - 8.00
 - 7.75
 - 8.00
 - 8.00
 - 17.00
 - S/S LIGHT SHIELD
 - 8.00
 - 2.00
 - 45.00
 - 114.50 CA
 - 66.00
 - 184.50 WB
 - 377.50 (31' - 2.50") APPROX OAL
 - 70.00
 - 91.00
 - JUMPER STUDS
 - AIR INLET/OUTLET WITH DISCONNECT FITTING
 - BLUE SEA SURE EJECT 7851 SHORELINE 20A 120V

HOSEBED CAPACITY	
BED 1	400' OF 2.50" D.J. POLY HOSE
BED 2	1000' OF 5.00" D.J. POLY HOSE
BED 3	400' OF 3.00" D.J. POLY HOSE

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

REV	DATE	BY	CH	SABER FR
27SEP23	RWR	JAP		
06JUL23	KLE	JAP		

Pierce MANUFACTURING INC.		JOB NO.	40563
		SCALE	1:24
		DATE	
		DRAWN BY	MMF
		01MAY23	
		CHECKED BY	COL
		02MAY23	
		SHEET SIZE	D
		SHEET NO.	1 OF 1

TITLE	Pierce Pumper Approval Drawing
FOR	Siddons Martin Sales
DWG NO.	40563AD

View File Created 26-SEP-2023 14:43:25